

255 ULTRA 2-WAY

COMPLETE MORE DELIVERIES & GET IN AND OUT FASTER.

The **Loadmac 255 Ultra 2-Way** helps your fleet unload quickly, preserve more legal payload, and handle deliveries with a compact, easy-to-run machine built for real jobsites.



When space is tight, time is limited, and every stop needs to move fast, the 255 2-Way gives your drivers the reach, simplicity, and control to get in, unload, and get back on the road.

Stop Letting Tight Jobsites Slow Everything Down

Standard setups don't just waste time. They make tight deliveries harder, reduce efficiency, and force your drivers to work around limitations instead of getting the job done.

-  Losing valuable payload to heavier forklift setups that reduce your margins
-  Struggling to maneuver bulky equipment in tight or restricted job sites
-  Frustrating drivers with awkward climbs and hard-to-use machines
-  Slowing down operations with complicated controls and hard-to-train equipment
-  Risking downtime when service, training, or parts are hard to find



Unload Faster. Fit Anywhere. And Stay On The

The 255 2-Way is built for compact performance—helping your fleet move faster, fit tighter spaces, and complete every delivery with confidence.

-  Lighter machine, but with more stability—preserving more legal payload on every run
-  Compact with a low-center design that keeps loads stable & easy to maneuver at full capacity
-  Man-on-ground mounting for safer, faster everyday use
-  No complex electronics—just reliable, easy-to-run equipment that keeps drivers moving
-  U.S. support, hands-on training, and ready access to parts

LOADMAC 255 ULTRA 2-WAY

Truck Mounted Forklift | Compact | Integrated Reach

Specifications	Details
PERFORMANCE & CAPACITY	
Rated Capacity	5,500 lbs
Maximum Reach	40"
Lift Height	Up to 10' (120")
Gradeability	49%
Travel Speed	7.5 MPH
ENGINE & POWERTRAIN	
Engine Make	Kubota
Horsepower	25 HP
Cylinders	3
Fuel Type	Diesel
Drive System	Hydrostatic
Emission Standard	EPA Tier 4 Final
Max Engine RPM	2,600
DIMENSIONS & WEIGHT	
Overall Length (w/48" forks)	87"
Overall Width	90"
Overall Height	97"
Wheelbase	61"
Turning Radius	61"
Unladen Weight	4,495-4,880 lbs

Specifications	Details
FORKS, REACH & MAST	
Mast Type	Fixed w/IR
Mast Travel	0"
Reach Extension	40"
Total Forward Reach	40"
Fork Section	48" x 4" x 2"
Carriage Width	47.25" (Class II)
Side Shift	6"
Carriage Tilt	6.5° forward / 12° backward
DRIVE, TIRES & TERRAIN	
Drive Wheels	3
Steering	2-Way
Steering Type	Hydrostatic
Rear Steering Rotation	180°
Tires (Front)	23" x 8.5" - 12 ply
Tires (Rear)	27" x 10.5" - 8 ply
Equipment Ground Clearance	8"
GENERAL SPECIFICATIONS	
Operator Position	Seated
Frame Opening	60"
Overhang	45.3"
Hydraulic Pressure	200 / 350 bar (≈ 2,900 / 5,076 psi)
Compliance	ANSI B56.14



Built for true delivery independence. Rethinking what truck mounted forklifts should deliver.