

255 ULTRA 4-WAY

COMPLETE MORE DELIVERIES & HANDLE TIGHT JOBSITES WITH EASE.

The **Loadmac 255 Ultra 4-Way** helps your fleet unload with confidence, preserve more legal payload, and move through tight jobsites with greater control and flexibility.



When space is limited, access is tight, and materials are difficult to position, the 255 4-Way gives your drivers the maneuverability, reach, and control to finish the drop and move on.

Stop Letting Tight Jobsites Slow Down Deliveries

Alternative setups don't just waste time. They make tight deliveries harder, limit where you can unload, and force your drivers to work around the jobsite instead of through it.

-  Trying to maneuver in tight sites, crowded delivery zones, and around long materials
-  Losing valuable payload to heavier forklift setups that reduce your margins
-  Frustrating drivers with awkward climbs and hard-to-use machines
-  Slowing down operations with complicated controls and hard-to-train equipment
-  Risking downtime when service, training, or parts are hard to find



Move Freely. Unload Faster. And Stay On The

The 255 4-Way is built for compact maneuverability—helping your fleet move through tight spaces, unload faster, and complete every drop with confidence.

-  4-way maneuverability for tighter sites, long materials, and crowded delivery zones
-  Lighter machine, but with more stability—preserving more legal payload on every run
-  Man-on-ground mounting for safer, faster everyday use
-  No complex electronics—just reliable, easy-to-run equipment that keeps drivers moving
-  U.S. support, hands-on training, and ready access to parts

LOADMAC 255 ULTRA 4-WAY

Truck Mounted Forklift | Compact | Multidirectional

Specifications	Details
PERFORMANCE & CAPACITY	
Rated Capacity	5,500 lbs @ 24" load center
Maximum Reach	40"
Lift Height	Up to 10' (120")
Gradeability	49%
Travel Speed	7.5 MPH
ENGINE & POWERTRAIN	
Engine Make	Kubota
Horsepower	25 HP
Cylinders	3
Fuel Type	Diesel
Drive System	Hydrostatic
Emission Standard	EPA Tier 4 Final
Max Engine RPM	2,600
DIMENSIONS & WEIGHT	
Overall Length (w/48" forks)	91"
Overall Width	90"
Overall Height	97"
Wheelbase	61"
Turning Radius	61"
Unladen Weight	4,710-5,095 lbs

Specifications	Details
FORKS, REACH & MAST	
Mast Type	Fixed w/IR
Mast Travel	0"
Reach Extension	40"
Total Forward Reach	40"
Fork Section	48" x 4" x 2"
Carriage Width	47.25" (Class II)
Side Shift	6"
Carriage Tilt	6.5° forward / 12° backward
DRIVE, TIRES & TERRAIN	
Drive Wheels	3
Steering	Multidirectional 4-Way
Steering Type	Hydrostatic
Rear Steering Rotation	180°
Tires (Front)	23" x 8.5" - 6 ply
Tires (Rear)	27" x 10.5" - 8 ply
Equipment Ground Clearance	8"
Stabilizer Clearance	6"
GENERAL SPECIFICATIONS	
Operator Position	Seated
Frame Opening	60"
Overhang	45.3"
Hydraulic Pressure	200 / 350 bar (≈ 2,900 / 5,076 psi)
Compliance	ANSI B56.14



Built for true delivery independence. Rethinking what truck mounted forklifts should deliver.