

855 SUPER REACH 2-WAY

COMPLETE MORE DELIVERIES & KEEP JOBSITES MOVING.

The **Loadmac 855 Super Reach 2-Way** helps your fleet offload from one side, preserve more legal payload, and complete deliveries faster with simple, reliable operation.



When site access is limited, time is tight, and every pound matters, the 855 2-Way gives your drivers the reach, simplicity, and control to finish the drop and move on.

Stop Letting Jobsite Delays Slow You Down

Standard setups do more than waste time. They cut into your payload, slow down unloading, and make every delivery harder than it needs to be.

-  Burning time repositioning the truck to reach the far side of the load
-  Losing valuable payload to heavier forklift setups that reduce your margins
-  Frustrating drivers with awkward climbs and hard-to-use machines
-  Slowing down operations with complicated controls and hard-to-train equipment
-  Risking downtime when service, training, or parts are hard to find



Unload Faster. Carry More. And Stay On The

The 855 2-Way is built for efficient, one-sided offloading—helping your fleet move faster, carry more, and complete every drop with confidence.

-  Reach across the bed and offload from one side with standard Super Reach
-  Lighter machine, but with more stability—preserving more legal payload on every run
-  Man-on-ground mounting for safer, faster everyday use
-  No complex electronics—just reliable, easy-to-run equipment that keeps drivers moving
-  U.S. support, hands-on training, and ready access to parts

LOADMAC 855 SUPER REACH 2-WAY

Truck Mounted Forklift | One-Side Offload | Extended Reach

Specifications	Details
PERFORMANCE & CAPACITY	
Rated Capacity	5,500 lbs @ 24" load center
Capacity (Extended Reach)	5,500 lbs (against truck/trailer bed)
Maximum Reach	84"
Lift Height	Up to 12' (144")
Gradeability	35%
Travel Speed	9 MPH
ENGINE & POWERTRAIN	
Engine Make	Hatz
Horsepower	56 HP
Cylinders	3
Fuel Type	Diesel
Drive System	Hydrostatic
Emission Standard	EPA Tier 4 Final
Max Engine RPM	2,800
DIMENSIONS & WEIGHT	
Overall Length (w/48" forks)	106"
Overall Width	93"
Overall Height	109"
Wheelbase	64"
Turning Radius	64"
Unladen Weight	6,200-6,870 lbs

Specifications	Details
FORKS, REACH & MAST	
Mast Type	Two Stage
Mast Travel	44"
Pantograph Extension	40"
Total Forward Reach	84"
Fork Section	48" x 6" x 1.5"
Carriage Width	47.25" (Class III)
Side Shift	6"
Carriage Tilt	12° forward / 10° backward
DRIVE, TIRES & TERRAIN	
Drive Wheels	3
Steering	2-Way
Steering Type	Hydrostatic
Rear Steering Rotation	180°
Tires (Front)	29" x 12.5" - 15 dia - 8 ply
Tires (Rear)	31" x 15.5" - 15 dia - 8 ply
Equipment Ground Clearance	12"
Stabilizer Clearance	6.5"
GENERAL SPECIFICATIONS	
Operator Position	Seated
Frame Opening	65"
Overhang	53"-59"
Hydraulic Pressure	250 / 350 bar (= 3,625 / 5,076 psi)
Compliance	ANSI B56.14



Built for true delivery independence. Rethinking what truck mounted forklifts should deliver.