

855 SUPER REACH 4-WAY

COMPLETE MORE DELIVERIES & STOP LOSING TIME ON JOBSITES.

The **Loadmac 855 Super Reach 4-Way** helps your fleet offload from one side, preserve more legal payload, and handle tight jobsites with more speed and control.



When site access is tight, no forklift is waiting, and the schedule cannot slip, the 855 4-Way gives your drivers the reach, maneuverability, and man-on-ground simplicity to finish the drop and move on.

Stop Letting the Jobsite Control the Route

Alternative setups do more than slow you down. They eat into margin, frustrate drivers, and make every delivery harder and less safe than it should be.



Trying to maneuver in tight sites, crowded delivery zones, and around long materials



Burning time repositioning the truck to reach the far side of the load



Losing valuable payload to heavier forklift setups that reduce your margins



Frustrating drivers with awkward climbs and hard-to-use machines



Risking downtime when service, training, or parts are hard to find



Carry More. Unload Faster & Easier. And Stay On The

The 855 4-Way is packed with more features, built to help you unload faster, protect your profit, and make every drop more predictable, even in uneven, muddy terrain.



4-way maneuverability for tighter sites, long materials, and crowded delivery zones



Reach across the bed and offload from one side with standard Super Reach



Lighter machine, but with more stability—preserving more legal payload on every run



Man-on-ground mounting for safer, faster everyday use with reliable, easy to run equipment



U.S. support, hands-on training, and ready access to parts

LOADMAC 855 SUPER REACH 4-WAY

Truck Mounted Forklift | Multidirectional | Extended Reach

Specifications	Details
PERFORMANCE & CAPACITY	
Rated Capacity	5,500 lbs @ 24" load center
Capacity (Extended Reach)	5,500 lbs (against truck/trailer bed)
Maximum Reach	84"
Lift Height	Up to 12' (144")
Gradeability	35%
Travel Speed	9 MPH
ENGINE & POWERTRAIN	
Engine Make	Hatz
Horsepower	56 HP
Cylinders	3
Fuel Type	Diesel
Drive System	Hydrostatic
Emission Standard	EPA Tier 4 Final
Max Engine RPM	2,800
DIMENSIONS & WEIGHT	
Overall Length (w/48" forks)	99"
Overall Width	99"
Overall Height	108"
Wheelbase	80"
Turning Radius	64"
Unladen Weight	6,320-6,815 lbs

Specifications	Details
FORKS, REACH & MAST	
Mast Type	Two Stage
Mast Travel	44"
Pantograph Extension	40"
Total Forward Reach	84"
Fork Section	48" x 6" x 1.5"
Carriage Width	47.25" (Class III)
Side Shift	6"
Carriage Tilt	12° forward / 10° backward
DRIVE, TIRES & TERRAIN	
Drive Wheels	3
Steering	Multidirectional 4-Way
Steering Type	Hydrostatic
Rear Steering Rotation	180°
Tires (Front)	29" x 12.5" - 15 dia - 8 ply
Tires (Rear)	29" x 12.5" - 15 dia - 8 ply
Equipment Ground Clearance	12"
Stabilizer Clearance	6.5"
GENERAL SPECIFICATIONS	
Operator Position	Seated
Frame Opening	64"
Overhang	53"-59"
Hydraulic Pressure	250 / 350 bar (= 3,625 / 5,076 psi)
Compliance	ANSI B56.14



Built for true delivery independence. Rethinking what truck mounted forklifts should deliver.